

TECHNICAL MANUAL

NO. 5-855-4

HEADQUARTERS
DEPARTMENT OF THE ARMY
Washington, D.C. 28 November 1986

HEATING, VENTILATION, AND AIR CONDITIONING OF HARDENED INSTALLATION

TABLE OF CONTENTS

	Paragraph	Page
CHAPTER 1. INTRODUCTION		
Purpose	1-1	1-1
Scope	1-2	1-1
Criteria	1-3	1-1
Operating modes	1-4	1-2
Hardened configurations	1-5	1-3
CHAPTER 2. DESIGN CONSIDERATIONS		
General	2-1	2-1
Makeup air	2-	2-1
Combustion air	2-3	2-2
Vitiated air	2-4	2-3
Temperature and humidity	2-5	2-6
Internal loads	2-6	2-8
External loads	2-7	2-9
Moisture loads	2-8	2-10
Air distribution and fire protection	2-9	2-11
(CBR) protection	2-10	2-12
Economic factors	2-11	2-16
Survivability and reliability	2-12	2-12
CHAPTER 3. UNDERGROUND HEAT TRANSFER		
Underground heat conduction fundamentals	3-1	3-1
Underground conduction standard calculation method	3-2	3-2
Underground conduction shortcut calculation method	3-3	3-10
Tunnel intake air tempering	3-4	3-15
Thermal properties of rock	3-5	3-18
Thermal properties of materials and structures	3-6	3-26
Conversion time duration	3-7	3-26
Trend analysis	3-8	3-26
Sample problems	3-9	3-33
CHAPTER 4. HVAC EQUIPMENT		
General	4-1	4-1
Air cleaners	4-2	4-1
CBR filters	4-3	4-3
Coils and piping	4-4	4-7
Refrigeration equipment	4-5	4-9
Fans	4-6	4-9
Duct systems	4-7	4-9
Humidity control systems	4-8	4-10
Computer area cooling	4-9	4-11
Boilers and heat recovery	4-10	4-11

28 November 1986

	<i>Paragraph</i>	<i>Page</i>
CHAPTER 5.	WASTE HEAT DISPOSAL	
	Heat sinks	5-1
	Once through and recirculated reservoirs	5-1
	Iced reservoirs	5-3
	Solid ice heat sinks	5-4
	Sample problems	5-5
	Cooling towers	5-12
	Radiators	5-14
CHAPTER 6.	DECONTAMINATION FACILITIES	
	General	6-1
	Entrances	6-2
	Decontamination	6-5
	Ventilation	6-9
APPENDIX A.	REFERENCES	A-1
APPENDIX B.	UNITS, SYMBOLS, AND EQUATION	B-1
GLOSSARY		Glossary

LIST OF FIGURES

Figure 3-1.	Wall flux ratio of equivalent cylinder or sphere.	3-5
3-2.	Thermal resistance factor, cylinder model, warm-up.	3-6
3-3.	Thermal resistance factor, sphere model, warm-up.	3-7
3-4.	Thermal conductance factor, cylinder model, holding.	3-6
3-5.	Thermal conductance factor, sphere model, holding.	3-9
3-6.	Underground cavity, typical isotherms.	3-11
3-7.	Rock shell volume isometric.	3-12
3-8.	Typical warm-up temperature profiles.	3-13
3-9.	Volume averaged rock shell temperature ratio.	3-14
3-10.	Tunnel air temperature, amplitude and lag factors.	3-17
3-11.	Density and thermal conductivity of igneous rocks.	3-21
3-12.	Unfrozen silt and clay soils conductivity.	3-22
3-13.	Frozen silt and clay soils conductivity.	3-23
3-14.	Unfrozen sandy soil conductivity.	3-24
3-15.	Frozen sandy soil conductivity.	3-25
3-16.	Warm-up heat flux for $k = 1.2$ and 25° F differential.	3-29
3-17.	Warm-up heat flux for $k = 1.7$ and 27° F differential.	3-30
3-18.	Holding heat flux for $k = 1.2$ and 25° F differential.	3-31
3-19.	Holding heat flux for $k = 1.7$ and 25° F differential.	3-32
4-1.	CB particulate and gas filter.	4-4
4-2.	CB gas filter model FFU-17/E.	4-5
4-3.	CB filter assembly.	4-6
4-4.	Bladder-type attenuator for chilled water.	4-8
5-1.	Typical hardened cooling water system.	5-13
6-1.	Corridor type decontamination facility retrofit.	6-3
6-2.	M2 permeable membrane door.	6-4
6-3.	Dual decontamination facility.	6-6
6-4.	Decontamination facility sized for 18 people per hour.	6-7
6-5.	Contaminated clothes chute.	6-8
6-6.	Air pressure regulator M-1.	6-10
6-7.	Antiback-draft valve.	6-11

LIST OF TABLES

Table 2-1.	Typical personnel metabolic rates.	2-4
2-2.	Properties of air regeneration chemicals.	2-5
2-3.	Humidity tolerance of selected materials.	2-6
2-4.	Particulate filters.	2-15
2-5.	Gas filters.	2-15
3-1.	Typical thermal properties of various materials.	3-20
3-2.	Selected parameters for trend analysis.	3-28
4-1.	Performance of dry media particulate filters.	4-2
5-1.	Comparison of 10-day capacity heat sinks.	5-7
5-2.	Reservoir length versus time at fixed 400 ft section	5-9